A Representative Examples from MME-VideoOCR

To comprehensively illustrate the characteristics of tasks in MME-VideoOCR, we present one representative example for each task.



Figure 7: An example QA of the Text Recognition at Designated Locations task in MME-VideoOCR.




Figure 8: An example QA of the Text Recognition Based on Specific Attributes task in MME-VideoOCR.




Figure 9: An example QA of the Text-Centric QA task in MME-VideoOCR.




Figure 10: An example QA of the Translation task in MME-VideoOCR.




Figure 11: An example QA of the Spatial Grounding task in MME-VideoOCR.




Figure 12: An example QA of the Temporal Grounding task in MME-VideoOCR.



Figure 13: An example QA of the Change Detection task in MME-VideoOCR.




Figure 14: An example QA of the Tracking task in MME-VideoOCR.




Figure 15: An example QA of the Complex Reasoning task in MME-VideoOCR.




Figure 16: An example QA of the Subtitle-Based Video Understanding task in MME-VideoOCR.




Figure 17: An example QA of the Multi-Hop Needle in A Haystack task in MME-VideoOCR.




Figure 18: An example QA of the Table Parsing task in MME-VideoOCR.




Figure 19: An example QA of the Chart Parsing task in MME-VideoOCR.




Figure 20: An example QA of the Document Parsing task in MME-VideoOCR.




Figure 21: An example QA of the Mathematical Formula Parsing task in MME-VideoOCR.




Figure 22: An example QA of the Handwriting Recognition task in MME-VideoOCR.




Figure 23: An example QA of the Color Recognition task in MME-VideoOCR.



Figure 24: An example QA of the Named Entity Recognition task in MME-VideoOCR.




Figure 25: An example QA of the Counting task in MME-VideoOCR.




Figure 26: An example QA of the Scrolling Text Understanding task in MME-VideoOCR.




Figure 27: An example QA of the Trajectory Recognition task in MME-VideoOCR.




Figure 28: An example QA of the Scrambled Recognition task in MME-VideoOCR.



Figure 29: An example QA of the AIGC Video task in MME-VideoOCR.




Figure 30: An example QA of the Adversarial Video task in MME-VideoOCR.




Figure 31: An example QA of the Long Video task in MME-VideoOCR.

B Benchmark Details

B.1 Task Definition

MME-VideoOCR collects 10 OCR task categories. Detailed definition of the taxonomy is depicted as below.

Text Recognition. Text Recognition is a fundamental OCR task that evaluates an MLLM's ability to perceive and interpret text. This category involves *Text Recognition at Designated Locations* and *Text Recognition Based on Specific Attributes*. These two subtasks can be flexibly combined to assess an MLLM's capacity for fine-grained text recognition. For instance, a query may require recognizing text specifically located on a license plate and written in a particular language or color, thereby evaluating both spatial awareness and attribute-based recognition within complex visual scenes.

Visual Text QA. Visual Text QA encompasses two tasks: *Text-Centric QA* and *Translation. Text-Centric QA* requires models to integrate textual content with relevant visual cues to answer context-dependent questions. *Translation* focuses on converting specific on-screen text into a designated target language. Both tasks challenge the model's ability to not only perceive but also comprehend multimodal information.

Text Grounding. Text Grounding involves *Spatial Grounding* and *Temporal Grounding*. *Spatial Grounding* concerns identifying the location of specified text based on visual context—such as recognizing that the text appears on a street sign or a product label—rather than relying on exact coordinates. *Temporal Grounding* centers on understanding the temporal properties of text, including when it appears, how long it remains visible, and the sequence in which it occurs. Together, these subtasks assess the model's ability to localize and interpret text across both spatial and temporal dimensions within dynamic visual scenes.

Attribute Recognition. This category is composed of three tasks: *Color Recognition*, where models are expected to identify the color of the text; *Named Entity Recognition*, which focuses on extracting and classifying named entities such as person names, organization names, and location names; and *Counting*, where models must accurately identify the number of textual elements that meet specified criteria.

Change Detection & Tracking. The task consists of two tasks: Change Detection and Tracking. Given the highly dynamic nature of text in video, Change Detection aims to accurately identify changes in textual content over time. Tracking, on the other hand, focuses on monitoring text elements as they change position across frames—for example, tracing the movement of a vehicle with a specified license plate number or identifying the player running with the ball based on their jersey number.

Special Text Parsing. Special Text Parsing includes five tasks: *Table Parsing*, *Chart Parsing*, *Document Parsing*, *Mathematical Formula Parsing*, and *Handwriting Recognition*. These tasks require models to accurately identify and understand text with either special structures or highly variable visual forms.

Cross-Frame Text Understanding. In video scenarios, relying on a single frame is often insufficient, as critical information may be distributed across multiple frames and closely interrelated. To address this, the task of Cross-Frame Text Understanding is introduced, which requires models to integrate information across multiple frames for coherent interpretation. It includes three subtasks: *Scrolling Text Understanding*, which focuses on recognizing dynamic text streams—such as on-screen bullet comments—that move across frames and may only be fully readable when aggregated over time; *Trajectory Recognition*, where the motion path of an object in the video forms a recognizable text, and the model must interpret this trajectory as the intended message; *Scrambled Recognition*, which involves identifying and reconstructing a complete text from characters that appear out of order across different positions in the video frames.

Text-Based Reasoning. Text-Based Reasoning, also referred to as *Complex Reasoning*, emphasizes advanced understanding of textual content, such as code analysis, mathematical operations, and logical reasoning. Unlike *Text-Centric QA*, which is a straightforward comprehension task centered on identifying explicit information, *Complex Reasoning* requires models to go beyond surface-level understanding by synthesizing dispersed textual cues, identifying implicit relationships, and resolving ambiguity or misleading content.

Text-Based Video Understanding. Current video understanding tasks are primarily based on visual dynamics, such as action recognition and video captioning. However, these tasks often overlook the textual information in videos, even though they are essential for video understanding in certain contexts. To address this gap, we introduce *Subtitle-Based Video Understanding*. In this task, the answer to a question is hidden in the subtitles, and MLLMs must combine subtitle information with visual content to answer correctly. This reflects real-world scenarios like conversations, tutorials, or news, where subtitles provide key information that visuals alone cannot capture. *Multi-Hop Needle in A Haystack* is a novel and effective task introduced in VideoChat-Flash [47], designed to test models' ability to retrieve information from videos based on subtitles that are spread across multiple frames. It requires reasoning over multiple pieces of subtitle content to find the correct answer.

Robust Video Testing. To evaluate model effectiveness and robustness across diverse scenarios, we introduce three specialized video types: AIGC Videos, Long Videos, and Adversarial Videos. AIGC Videos, generated by AI systems [42], assess model adaptability to increasingly common synthetic content. Long Videos test the ability to extract relevant information from lengthy sequences with substantial redundancy. Since existing MLLMs primarily process videos by extracting frames, we construct a set of Adversarial Videos by strategically inserting all-black frames into normal videos. While these adversarial samples have minimal impact on human perception, they can easily mislead the model, rendering it virtually "blind".

B.2 Task Distribution

Table 5: Number of QA Pairs per task in MME-VideoOCR.

Task Category	Task				
Tayt Daggarition	Text Recognition at Designated Locations	200			
Text Recognition	Text Recognition Based on Specific Attributes	100			
Visual Text QA	Text-Centric QA	250			
visual lext QA	Translation	50			
Text Grounding	Spatial Grounding	100			
Text Grounding	Temporal Grounding	100			
	Color Recognition	50			
Attribute Recognition	Named Entity Recognition	50			
	Counting	50			
Change Detection & Tracking	Change Detection	100			
Change Detection & Tracking	Tracking	100			
	Table Parsing	50			
	Chart Parsing	50			
Special Text Parsing	Document Parsing	50			
Special Text Parsing	Mathematical Formula Parsing	50			
	Handwriting Recognition	50			
	Scrolling Text Understanding	50			
Cross-Frame Text Understanding	Trajectory Recognition	50			
	Scrambled Recognition	50			
Text-Based Reasoning	Complex Reasoning	150			
Taxt Based Video Understanding	Subtitle-Based Video Understanding	100			
Text-Based Video Understanding	Multi-Hop Needle in a Haystack	100			
	AIGC Videos	50			
Robust Video Testing	Long Videos	50			
-	Adversarial Videos	50			
Total	-	2,000			

Given the diverse range of task types included in MME-VideoOCR, which assess a broad spectrum of model capabilities, we carefully allocate the number of QA pairs across different tasks. Table 5

Table 6: Evaluation prompt setting of MME-VideoOCR (Containment Match).

[Video]

Based on the video and the question below, directly answer the content that needs to be recognized in plain text. Do not include any additional explanations, formatting changes, or extra information. Question: [Question]

The answer is:

Table 7: Evaluation prompt setting of MME-VideoOCR (GPT-Assisted Scoring).

[Video]

Based on the video and the question below, directly provide the answer in plain text. Do not include any additional explanations, formatting changes, or extra information.

Question: [Question]

The answer is:

presents the specific number of QA pairs for each task. This allocation ensures a balanced distribution among perception, understanding, and reasoning tasks, thereby supporting a comprehensive and equitable evaluation of model capabilities.

B.3 Evaluation Prompt

The prompt settings for Containment Match, GPT-Assisted Scoring and Multiple-Choice are shown in Table 6, Table 7 and Table 8. For GPT-Assisted Scoring (designed for the Translation task), after obtaining the model's response using the prompt shown in Table 7, we subsequently utilize GPT-40-0806 to evaluate the response. The corresponding evaluation prompt is provided in Table 9.

C Experiment Details

C.1 Evaluated Models

We evaluate a total of 18 mainstream MLLMs, including 3 leading proprietary models and 15 high-performing open-source models.

For proprietary models, we evaluate GPT-40 [56], Gemini-2.5 Pro [57] and Gemini-1.5 Pro [5].

- *GPT-4o* is the latest multimodal large language model developed by OpenAI, offering fast and cost-effective performance across text, image, and audio modalities. It achieves state-of-the-art results on a variety of benchmarks, with notable improvements in visual reasoning, OCR, and multilingual understanding. GPT-4o features a unified architecture that enables seamless cross-modal interaction, making it highly efficient and versatile for real-world multimodal applications.
- *Gemini-2.5 Pro* is one of the latest Multimodal Large Language Models released by Google DeepMind. It features improved visual and video understanding capabilities, with support for extended context lengths and more efficient cross-modal alignment. Gemini-2.5 Pro demonstrates strong performance across a wide range of tasks, including video captioning, image reasoning, and OCR-based understanding. Its enhanced architecture and training scale make it particularly competitive in complex multimodal benchmarks.
- Gemini-1.5 Pro, an earlier version in the Gemini series, also supports multimodal input
 and is optimized for high-quality text generation and basic vision-language tasks. While
 it delivers reliable performance on standard image-based benchmarks, its video comprehension ability—especially in tasks requiring temporal reasoning and dense visual-textual
 alignment—is more limited compared to its successor. Nevertheless, it remains a strong
 baseline among proprietary models.

For open-source models, we select Qwen2.5-VL [30], LLaVA-Video [29], LLaVA-OneVision [58], VideoLLaMA 3 [61], VideoChat-Flash [47], Oryx-1.5 [60], Slowfast-MLLM [62], InternVL3 [64], VITA-1.5 [2] and Kimi-VL [59]. Among them, for Oryx-1.5, Qwen2.5-VL, and InternVL3, we include versions with different parameter scales in our experiments.

Table 8: Evaluation prompt setting of MME-VideoOCR (Multiple-Choice).

[Video]

Select the best answer to the following multiple-choice question based on the video. Respond with only the letter (A, B, C, or D) of the correct option.

Ouestion: [Question]

Option:

A. [Option A]

B. [Option B]

C. [Option C]

D. [Option D]

The best answer is:

Table 9: Evaluation prompt setting of the Translation task.

You are a professional bilingual translation evaluator.

Here are two sentences: one in Chinese and one in English.

Sentence 1: [Ground Truth]
Sentence 2: [MLLM's Response]

Please evaluate whether the two sentences convey the same meaning and can be considered accurate translations of each other.

If the meanings are equivalent and the translation is accurate, respond with "correct".

If there are significant differences in meaning or inaccuracies in translation, respond with "wrong".

You must only respond with one word: "correct" or "wrong". Do not provide any explanations, comments, or additional text.

Focus solely on semantic equivalence, not grammar or style. Ignore minor differences as long as the meaning is preserved.

- Qwen2.5-VL is a vision-language model that introduces two key innovations: native dynamic-resolution processing and Multi-scale Rotary Position Embedding (MRoPE). The dynamic-resolution capability allows the model to process images and videos of varying resolutions and frame rates efficiently, extending to the temporal dimension through dynamic FPS sampling. This enables precise temporal event localization in long videos. MRoPE enhances the model's ability to capture multi-scale positional information, improving its performance in tasks requiring fine-grained spatial and temporal understanding.
- *LLaVA-Video* extends the LLaVA framework to video understanding by unifying visual representations into the language feature space. This alignment before projection enables the model to perform visual reasoning on both images and videos simultaneously. By training on a mixed dataset of images and videos, LLaVA-Video leverages mutual enhancement between modalities, achieving superior performance across various visual-language tasks.
- LLaVA-OneVision is designed for versatile visual task transfer across single-image, multiimage, and video scenarios. It employs a SigLIP vision encoder and a Qwen2 language backbone, processing images with the Anyres technique to handle high-resolution inputs effectively. Videos are processed with a fixed token length per frame for memory efficiency. This architecture enables LLaVA-OneVision to excel in diverse visual-language tasks without task-specific fine-tuning.
- *VideoLLaMA 3* is a vision-centric multimodal foundation model that advances image and video understanding. It utilizes Any-resolution Vision Tokenization (AVT) to process images and videos of varying resolutions dynamically. The model's training paradigm emphasizes high-quality image-text data to enhance video understanding capabilities. VideoLLaMA 3 achieves state-of-the-art performance on multiple benchmarks by integrating vision-centric training and framework designs.
- *VideoChat-Flash* is a long-context video-language model that introduces a Hierarchical visual token Compression (HiCo) method, effectively reducing redundancy in long videos by compressing visual tokens from the clip-level to the video-level. This approach enables high-fidelity representation while significantly lowering computational costs. Coupled with

- a multi-stage short-to-long learning scheme and training on the LongVid dataset, VideoChat-Flash achieves state-of-the-art performance on both long and short video benchmarks.
- Oryx-1.5 presents a unified multimodal architecture designed for on-demand spatial-temporal
 understanding of images, videos, and multi-view 3D scenes. It features a dynamic compressor module that performs token compression and adaptive positional embedding, allowing
 the model to efficiently process visual inputs with arbitrary spatial sizes and temporal lengths.
 This flexibility enables Oryx-1.5 to seamlessly handle diverse visual inputs across various
 modalities.
- Slowfast-MLLM integrates the SlowFast dual-pathway architecture with a multimodal large
 language model to explicitly capture both coarse and fine-grained temporal dynamics. The
 slow branch models long-term context, while the fast branch focuses on short-term changes,
 enabling rich motion representation. This design enhances temporal alignment and supports
 detailed video-text interaction in tasks such as action question answering and event tracking.
- *InternVL3* is a powerful vision-language model that unifies visual grounding, dense captioning, and temporal understanding via a cross-modality fusion backbone. It introduces region-level supervision and multi-frame alignment strategies, significantly improving its spatial-temporal grounding capabilities. InternVL3 demonstrates superior performance across a wide range of multimodal tasks, benefiting from its native multimodal pre-training paradigm and advanced post-training techniques.
- VITA-1.5 is a multimodal large language model designed to achieve real-time vision and speech interaction. It pioneers a meticulously crafted three-stage training strategy to effectively integrate vision, language, and speech modalities. This strategy systematically introduces visual and auditory data, mitigating conflicts between modalities while preserving robust multimodal capabilities. This methodology empowers VITA-1.5 to process and understand both visual and speech inputs and to generate fluent, end-to-end speech outputs, thereby enabling more natural and seamless interactive multimodal conversations.
- *Kimi-VL* is a state-of-the-art vision-language model developed by Moonshot AI, based on the Kimi series of large language models. Designed to handle complex multimodal tasks, Kimi-VL integrates high-resolution visual encoders with large-scale language understanding to enable robust performance in image captioning, visual question answering, and document understanding. It adopts a Mixture-of-Experts (MoE) architecture to improve inference efficiency, dynamically activating a subset of experts for each input. This design allows Kimi-VL to scale effectively while maintaining strong generalization across diverse visual-language benchmarks.

C.2 Experimental Setup

For proprietary models, we used the gpt-4o-2024-08-06, gemini-2.5-pro-preview-05-06 and gemini-1.5-pro-002 APIs, respectively.

In the MME-VideoOCR evaluation, most models were configured with a maximum input frame count of 64. GPT-40 was limited to 50 input frames due to API token constraints, while VITA-1.5 was restricted to 16 frames because of context length limitations. All other settings followed default or recommended configurations.

During the comparative experiments described in Section 4.2, the number of input frames was fixed at 32 when varying the resolution, while the default resolution settings were applied to all models when varying the number of input frames.

C.3 Experiment Results

Table 10, Table 11 and Table 12 present the complete results of evaluated models across all tasks in MME-VideoOCR.

D Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

Table 10: Accuracy of evaluated MLLMs on each task of MME-VideoOCR.

Text Recognition Text Recognition at Designated Locations Part Recognition Pesignated Locations Text Recognition Pesignated Locations Pesignated Locat	Task Category	Task	Gemini 1.5 Pro	Qwen2.5-VL 32B	InternVL 8B	Qwen2.5-VL 7B	Kimi-VL
Text Recognition Based on Specific Attributes 70.0% 65.0% 56.0% 71.0% 55.0%	Text Recognition		80.0%	55.0%	64.0%	70.0%	54.5%
Tack Translation So.0% 60.0% 58.0% 46.0% 58.0%			70.0%	65.0%	56.0%	71.0%	55.0%
Translation So.0% 60.0% S8.0% 46.0% S8.0%	Vigual Taxt OA	Text-Centric QA	83.0%	81.5%	75.5%	76.0%	68.5%
Temporal Grounding	visuai Text QA	Translation	56.0%	60.0%	58.0%	46.0%	58.0%
Color Recognition	Text Grounding		78.0%	73.0%	77.0%	77.0%	71.0%
Attribute Recognition Named Entity Recognition Counting 80.0% 52.0% 78.0% 50.0% 72.0% 56.0% 76.0% 70.0% 48.0% Change Detection & Tracking Change Detection 43.0% 40.0% 49.0% 40.0% 40.0% 33.0% 57.0% 33.0% 63.0% Tracking Tracking 67.0% 64.0% 64.0% 64.0% 57.0% 63.0% 57.0% 63.0% 54.0% 63.0% Special Text Parsing Table Parsing 72.0% 66.0% 56.0% 58.0% 54.0% 60.0% 60.0% 60.0% 68.0% 48.0% 54.0% 60.0% 60.0% 60.0% 68.0% 48.0% 54.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 6	Text Grounding	Temporal Grounding	45.0%	52.0%	43.0%	39.0%	47.0%
Counting 52.0% 50.0% 56.0% 52.0% 48.0%		Color Recognition	62.0%	78.0%	80.0%	78.0%	70.0%
Change Detection & Tracking Change Detection 43.0% 40.0% 49.0% 40.0% 33.0% Tracking Tracking 67.0% 64.0% 57.0% 63.0% Special Text Parsing Table Parsing 72.0% 66.0% 56.0% 58.0% 54.0% Chart Parsing 74.0% 60.0% 60.0% 68.0% 48.0% Special Text Parsing Document Parsing Mathematical Formula Parsing Handwriting Recognition 76.0% 76.0% 64.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0%	Attribute Recognition						
Tracking Tracking 67.0% 64.0% 64.0% 57.0% 63.0% Table Parsing 72.0% 66.0% 56.0% 58.0% 54.0% Chart Parsing 74.0% 60.0% 60.0% 68.0% 48.0% Document Parsing 80.0% 90.0% 72.0% 86.0% 74.0% Mathematical Formula Parsing 76.0% 76.0% 64.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 60.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0%		Counting	52.0%	50.0%	56.0%	52.0%	48.0%
Table Parsing	Change Detection &	Change Detection	43.0%	40.0%	49.0%	40.0%	33.0%
Chart Parsing	Tracking	Tracking	67.0%	64.0%	64.0%	57.0%	63.0%
Special Text Parsing Document Parsing Mathematical Formula Parsing Handwriting Recognition 80.0% 90.0% 72.0% 86.0% 74.0% Cross-Frame Text Understanding Understanding Scrolling Text Understanding Trajectory Recognition 72.0% 52.0% 70.0% 48.0% 70.0% Text-Based Reasoning Complex Reasoning 68.7% 52.0% 70.0% 48.0% 70.0% Text-Based Reasoning Complex Reasoning 68.7% 57.3% 49.3% 56.7% Text-Based Video Understanding Understanding 90.0% 93.0% 96.0% 90.0% 95.0% Text-Based Video Understanding Understanding 17.0% 16.0% 14.0% 16.0% 20.0% Robust Video Testing AIGC Videos 86.0% 66.0% 86.0% 78.0% 82.0% Adversarial Videos 76.0% 84.0% 78.0% 80.0% 78.0%		Table Parsing	72.0%	66.0%	56.0%		54.0%
Mathematical Formula Parsing Handwriting Recognition 76.0% 68.0% 64.0% 60.0% 60.0% 60.0% 60.0% 52.0% Cross-Frame Text Understanding Understanding Trajectory Recognition 72.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0%							
Handwriting Recognition	Special Text Parsing						
Cross-Frame Text Understanding Understanding Scrolling Text Understanding 72.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 70.0% 7							
Cross-Frame Text Understanding Trajectory Recognition Scrambled Recognition 0.0% 16.0% 16.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0%		Handwriting Recognition	68.0%	60.0%	60.0%	60.0%	52.0%
Trajectory Recognition 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0% 0.0	Cross-Frame Text						
Text-Based Reasoning Complex Reasoning 68.7% 68.7% 57.3% 49.3% 56.7%							
Text-Based Video Understanding Understanding Understanding Haystack Understanding Understanding Understanding Haystack Understanding Und	Onderstanding	Scrambled Recognition	22.0%	16.0%	0.0%	4.0%	0.0%
Text-Based Video Understanding Understanding Multi-Hop Needle in A Haystack 17.0% 16.0% 14.0% 16.0% 20.0% Robust Video Testing AIGC Videos Long Videos 86.0% 66.0% 86.0% 78.0% 82.0% Adversarial Videos 42.0% 46.0% 50.0% 56.0% 54.0% Adversarial Videos 76.0% 84.0% 78.0% 80.0% 78.0%	Text-Based Reasoning	Complex Reasoning	68.7%	68.7%	57.3%	49.3%	56.7%
Understanding Multi-Hop Needle in A Haystack 17.0% 16.0% 14.0% 16.0% 20.0% Robust Video Testing AIGC Videos 86.0% 66.0% 86.0% 78.0% 82.0% Long Videos 42.0% 46.0% 50.0% 56.0% 54.0% Adversarial Videos 76.0% 84.0% 78.0% 80.0% 78.0%			90.0%	93.0%	96.0%	90.0%	95.0%
Robust Video Testing Long Videos 42.0% 46.0% 50.0% 56.0% 54.0% Adversarial Videos 76.0% 84.0% 78.0% 80.0% 78.0%		Multi-Hop Needle in A	17.0%	16.0%	14.0%	16.0%	20.0%
Adversarial Videos 76.0% 84.0% 78.0% 80.0% 78.0%		AIGC Videos	86.0%	66.0%	86.0%	78.0%	82.0%
	Robust Video Testing		42.0%	46.0%	50.0%	56.0%	54.0%
Total - 64.9% 61.0% 59.8% 59.1% 56.2%	_	Adversarial Videos	76.0%	84.0%	78.0%	80.0%	78.0%
	Total	-	64.9%	61.0%	59.8%	59.1%	56.2%

Table 11: Accuracy of evaluated MLLMs on each task of MME-VideoOCR.

Task Category	Task	Oryx-1.5 32B	Video- LLaMA 3	LLaVA Video-7B	Oryx-1.5 7B
Text Recognition	Text Recognition at Designated Locations	52.5%	47.5%	49.0%	53.0%
	Text Recognition Based on Specific Attributes	46.0%	47.0%	43.0%	49.0%
V 1 T t O A	Text-Centric QA	67.0%	63.5%	67.0%	62.0%
Visual Text QA	Translation	32.0%	34.0%	28.0%	22.0%
Tt C 4:	Spatial Grounding	73.0%	65.0%	70.0%	59.0%
Text Grounding	Temporal Grounding	54.0%	71.0%	52.0%	42.0%
	Color Recognition	66.0%	76.0%	84.0%	64.0%
Attribute Recognition	Named Entity Recognition	68.0%	66.0%	66.0%	64.0%
2	Counting	54.0%	52.0%	56.0%	36.0%
Change Detection &	Change Detection	37.0%	39.0%	40.0%	35.0%
Tracking	Tracking	55.0%	61.0%	57.0%	54.0%
	Table Parsing	52.0%	44.0%	44.0%	50.0%
	Chart Parsing	46.0%	50.0%	42.0%	44.0%
Special Text Parsing	Document Parsing	76.0%	68.0%	64.0%	70.0%
	Mathematical Formula Parsing	74.0%	64.0%	56.0%	58.0%
	Handwriting Recognition	54.0%	44.0%	44.0%	42.0%
Cross-Frame Text	Scrolling Text Understanding	64.0%	60.0%	60.0%	68.0%
Understanding	Trajectory Recognition	0.0%	0.0%	0.0%	0.0%
Understanding	Scrambled Recognition	0.0%	4.0%	4.0%	2.0%
Text-Based Reasoning	Complex Reasoning	54.7%	48.7%	47.3%	48.7%
	Subtitle-Based Video	86.0%	91.0%	93.0%	78.0%
Text-Based Video	Understanding				
Understanding	Multi-Hop Needle in A Haystack	36.0%	19.0%	20.0%	16.0%
	AIGC Videos	80.0%	78.0%	86.0%	80.0%
Robust Video Testing	Long Videos	52.0%	56.0%	54.0%	40.0%
· ·	Adversarial Videos	72.0%	68.0%	66.0%	72.0%
Total	_	55.2%	53.5%	52.8%	49.6%

Table 12: Accuracy of evaluated MLLMs on each task of MME-VideoOCR.

Task Category	Task	VITA-1.5	Slow-fast MLLM	Videochat- Flash-7B	LLaVA OneVision-7F
Text Recognition	Text Recognition at Designated Locations	48.0%	46.0%	37.5%	42.0%
	Text Recognition Based on Specific Attributes	51.0%	46.0%	35.0%	42.0%
VC1 T+ O.A	Text-Centric QA	63.0%	61.5%	55.5%	57.0%
Visual Text QA	Translation	40.0%	28.0%	18.0%	22.0%
Text Grounding	Spatial Grounding	53.0%	61.0%	61.0%	58.0%
Text Grounding	Temporal Grounding	33.0%	43.0%	59.0%	40.0%
	Color Recognition	66.0%	66.0%	64.0%	66.0%
Attribute Recognition	Named Entity Recognition	58.0%	70.0%	66.0%	62.0%
	Counting	60.0%	44.0%	50.0%	34.0%
Change Detection &	Change Detection	37.0%	44.0%	43.0%	36.0%
Tracking	Tracking	61.0%	50.0%	55.0%	46.0%
	Table Parsing	44.0%	42.0%	32.0%	40.0%
	Chart Parsing	44.0%	42.0%	40.0%	40.0%
Special Text Parsing	Document Parsing	72.0%	64.0%	56.0%	56.0%
	Mathematical Formula Parsing	64.0%	60.0%	58.0%	56.0%
	Handwriting Recognition	42.0%	32.0%	44.0%	40.0%
Cross-Frame Text	Scrolling Text Understanding	60.0%	58.0%	58.0%	58.0%
Understanding	Trajectory Recognition	0.0%	0.0%	0.0%	0.0%
Onderstanding	Scrambled Recognition	0.0%	2.0%	0.0%	2.0%
Text-Based Reasoning	Complex Reasoning	51.3%	43.3%	50.0%	45.3%
Text-Based Video Understanding	Subtitle-Based Video	83.0%	83.0%	88.0%	86.0%
	Understanding Multi-Hop Needle in A	11.0%	14.0%	20.0%	18.0%
	Haystack	11.570	1 0 /0	20.070	10.070
	AIGC Videos	68.0%	58.0%	78.0%	78.0%
Robust Video Testing	Long Videos	42.0%	38.0%	44.0%	36.0%
C	Adversarial Videos	66.0%	66.0%	60.0%	66.0%
Total	_	49.5%	47.8%	47.8%	46.0%